

DG4301-0030-C810-B0

43" Closed Frame Touch Monitor



Multi-Touch

Aluminum Frame

PCAP



Application

- Self service
- Gaming
- Healthcare
- Industrial automation

Features

1. Integrated design with better stability and reliability.
2. Capacitive touchscreen for premium image quality and support 10-point touch.
3. $178^{\circ}(h) \times 178^{\circ}(v)$ visible angle, no matter mounted in landscape or portrait, also have optimal clarity and the viewing experience.
4. High-definition LCD displays offer superior high-definition interactivity, clarity and resolution.
5. 2-year warranty.



Specifications	
Part number	DG4301-0030-C810-B0
Enclosure color	Black
Active area	943.2 mm (H) x 531.4 mm (V) / 37.13" x 20.92"
Diagonal Size	43 inch
Aspect Ratio	16:9
Resolution	1920(H) × 1080(V)
Other Supported Resolutions	640x480 60Hz; 720x400 60Hz; 800x500, 60Hz; 800x600 60Hz; 1024x768 60Hz; 1280x800 60Hz; 1280x1024 60Hz; 1366x768 60Hz, 60Hz RB; 1440x900 60Hz, 60Hz RB; 1680x1050 60Hz, 60Hz RB;
Number of Colors	16.7M
Brightness (typical)	LCD panel: 400 nits
Response Time (typical)	8ms
Viewing Angle	178° (H) ; 178° (V)
Contrast Ratio	1200:1
On Screen Display	<p>Accessible through switches on the unit's tethered OSD Control box.</p> <p>Controls: Menu, Up, Down, Select, Power</p> <p>Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD timeout, OSD Language, OSD H-Position, OSD V-Position, Information</p> <p>Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese, Russian, Korean</p>
I/O Ports	Serial port (IntelliTouch only), USB Type B, RJ45 for OSD remote key, VGA, HDMI, Display Port, Receptacle Power Plug
Input Video Format&Frequency	<p>HDMI V1.3 Type A receptacle for HDMI input</p> <p>Analog VGA on Female DB-15 connector</p> <p>DisplayPort V1.1a - Supports later versions of DisplayPort video input</p> <p>Horizontal: 60 - 85 KHz</p> <p>Vertical: 48.3 - 63 Hz</p>
Power Supply	<p>Input voltage range: 100-240 VAC</p> <p>Input frequency: 50-60 Hz</p>
Power Consumption (Typical)	About 89W
Temperature	<p>Operating : 0°C ~ 40°C (32°F ~ 104°F) ;</p> <p>Storage: -20°C ~ 60°C (-4°F ~ 140°F)</p>
Humidity	Operating: 20% - 80%RH; Storage: 10% - 95%RH
Weight	Unpackaged: TBD kg; Packaged: TBD kg
Product Dimensions	1011.2 mm (L) x 599.4 mm (W) x 62 mm (H)
Shipping Box Dimensions	TBD mm (L) x TBD mm (W) x TBD mm (H)
Mounting Options	<p>200x200mm VESA mount on rear of unit.</p> <p>2 Hole mounting interface on all four sides.</p> <p>Flush mount with included brackets.</p>
Compliance	<p>ESD:15 kV air / 8 kV contact ESD compliant</p> <p>IK08 impact compliant</p>
Warranty	2-year
MTBF	50,000h

Regulatory approvals and declarations	CE or other according to customer requirements
Accessory for options	HDMI cable, VGA cable, OSD remote, Touch USB cable, OSD cable, Power Cable, Quick Install Guide, “L” (Side Mount) Brackets and w/Screws

DIGNITY

Dignity reserve the right to change or update products and documentation, and have the right to terminate or restrict the production and sale of products without prior notice.

Foshan Shunde Dignity Electronic Technology Co.,Ltd
 No.8, Chaoguang Mid-Road, Xiao Huangpu, Ronggui, Shunde,
 Foshan, Guangdong, China
Tel: +86 757 2668 7241
Fax: +86 757 2668 1196
<http://www.dignity.com.cn>